


7A20002



Copper Cable, category 7A, 4 pair simplex, S/FTP, LSFRZH, 23 AWG solid, 1000 m, white

Product Classification

Regional Availability	Australia/New Zealand EMEA
Portfolio	LITANG®
Product Type	Twisted pair cable

General Specifications

ANSI/TIA Category	7A
Cable Component Type	Horizontal
Cable Type	S/FTP (shielded)
Conductor Type, singles	Solid
Conductors, quantity	8
Jacket Color	White
Pairs, quantity	4
Transmission Standards	ANSI/TIA-568-C.2 CENELEC EN 50288-6-1 EN 50173-1 ISO/IEC 11801 Class E

Dimensions

Cable Length	3281 ft 1,000.049 m
Diameter Over Jacket, nominal	0.295 in 7.493 mm
Conductor Gauge, singles	23 AWG

Electrical Specifications

Operating Voltage, maximum	80 V
-----------------------------------	------

Material Specifications

Conductor Material	Bare copper
Insulation Material	Polyolefin

7A20002

Jacket Material	Low Smoke Fire Retardant Zero Halogen (LSFRZH)
Shield (Tape) Material	Aluminum/Polyester

Environmental Specifications

Operating Temperature	-20 °C to +60 °C (-4 °F to +140 °F)
EN50575 CPR Cable EuroClass	Dca a1 d1 s2

Packaging and Weights

Packaging Type	Reel
-----------------------	------

Regulatory Compliance/Certifications

Agency	Classification
CENELEC	EN 50575 compliant, Declaration of Performance (DoP) available
CHINA-ROHS	Below maximum concentration value
REACH-SVHC	Compliant as per SVHC revision on www.litangcables.com/ProductCompliance
ROHS	Compliant

